



ELECTRONIC SOLDERS

RMA ACTIVATED ROSIN CORE SOLDER For Lead-Bearing and Lead-Free Alloys

DESCRIPTION

BOW RMA flux is a mildly activated rosin formula for use in flux cored solder wire. Features of this flux are the instant wetting action and fast-spreading action.

FEATURES

- Mildly activated RMA formulation dependent on % halides
- Excellent solderability for a wide variety of applications
- Classified as ROM1 per J-STD-004

AVAILABILITY

Rosin Core may be obtained in a wide array of alloys, in diameters from .009 to .125 in flux percentages from 1.1% to 3.6%, packaged on 1, 5, and 20 pound spools.

RELIABILITY PROPERTIES

Copper Mirror Corrosion: Pass
Tested to J-STD-004, IPC-TM-650, Method 2.3.32

Corrosion Test: Pass
Tested to J-STD-004, IPC-TM-650, Method 2.6.15

Halogen Content: 0.5-2.0% ROM1

Appearance: White to yellowish solid

STORAGE AND SHELF LIFE

Store in any dry, non-corrosive environment. Cored wire solder has a shelf life of 2 years from date of manufacture.

1 Crossman Road South, Sayreville, N. J. 08872
Tel: 732-316-2100 ■ Fax: 732-316-2177 ■ Toll Free 800-526-4577

www.solders.com

