



**Canfield Technologies, LLC**

**TECHNICAL DATA SHEET  
ACTION-TIN TINNING PAINT**

The perfect soldering job is easy when you use Action-Tin Tinning Paint. Perfect soldering is achieved when the two surfaces in contact are metallurgically (mechanically and chemically) bonded together by the solder. The entire area is covered and there are no voids. Action-Tin wets each surface entirely which you can see before soldering.

Action-Tin is a mixture of tin and lead solder powder and a specially formulated chemical flux. It is thick and creamy so it stays where you put it. It pre-tins not only copper and brass, but harder to solder materials such as steel, iron, stainless steel, cast iron, beryllium copper, terne plate, lead flashings and coatings.

Action-Tin may be diluted with water when using in a tinning bath. Dilute to desired consistency and agitate bath to keep metal from settling

Contains no muriatic acid yet does a better job and works more actively than many fluxes do. As with all fluxes, make sure the area you are working in is well ventilated and follow proper procedures and precautions.

Also available in our lead-free formula – EnviroSafe Action-Tin. Safe for use on all sanitary, food and other environmentally sensitive applications.

**EASY TO USE  
HEAT PART, BRUSH ON ACTION-TIN AND IT'S SOLDERED**

1 Crossman Road South, Sayreville, NJ 08872  
Tel: 732-316-2100 ■ Toll Free 800-526-4577 ■ Fax: 732-316-2177  
[www.canfieldmetals.com](http://www.canfieldmetals.com)

